

POWER PACKS



K 1152 TS



K 1152 TST



K 2160 TS



K 2160 TST

Technical Specifications:

Order nr:	A412191	A412181	A417801	A417811
Operating pressure:	130 bar	130 bar	130 bar	130 bar
Water output:	10 l/min	10 l/min	10.5 l/min	10.5 l/min
Suction height:		-	2.5m	2.5m
Nozzle size, DK:	042	042	042	042
Nozzle size, flat jet lance:	042 vario jet	042 vario jet	042 standard	042 standard
Motor speed:	2800 rpm	2800 rpm	1400 rpm	1400 rpm
Load:	230 v	230 v	230 v	230 v
Power intake:	2.8 kw	2.8 kw	3.2 kw	3.2 kw
Power output:	2.1 kw	2.1 kw	2.4 kw	2.4 kw
Weight:	29 kg	31.5 kg	37 kg	39.5 kg
Dimensions (mm):	360 x 365 x 870	360 x 365 x 870	375 x 360 x 900	375 x 360 x 900

Equipment:

Total-Stop system:	Yes	Yes	Yes	Yes
Hose reel:	No	Yes	No	No
Low pressure detergent:	Yes	Yes	Yes	No
High pressure hose:	A43416 (10m)	A48015 (15m)	A43416 (10m)	A48015 (15m)
Gun & 1/2 lance:	A12480	A12480	A12480	A12480
Dirt killer c/w s/s pipe:	A41570 - 042	A41570 - 042	A41570 - 042	A41570 - 042
Flat jet nozzle c/w s/s pipe:	41156 - 042	41156 - 042	A12701 - 042	A12701 - 042

Spare Parts:

Water seals:	A49053	A49053	A410491	A410491
Oil seals:	3 x A41631	3 x A41631	3 x A41031	3 x A41031
Valves:	A41648	A41648	A417481	A417481
Un-loader valve:	A445321	A445321	A40490	A40490
In-line filter:	A410462	A410462	A410462	A410462
Pressure gauge:	A15039	A15039	A15039	A15039
On / off switch:	A43033	A43033	A411116	A411116
On / off switch cover:	A43453	A43453	A43453	A43453
Microswitch:	A15018	A15018	A15018	A15018
Green o ring (for lance):	A132731	A132731	A132731	A132731
Swashplate:	A41028 - 9.25°	A41028 - 9.25°	A41028 - 11.5°	A41028 - 11.5°
Pistons:	3 x A49021	3 x A49021	3 x A410321	3 x A410321
O ring on piston of UL:	A141231	A141231	A13159	A13159
Capacitor:	A43035	A43035	A43322	A43322
Wheel:	A44538	A44538	A44538	A44538