

## The Stationary Cold Water Series



**W 19/180**

### Technical Specifications:

Order nr with flow switch:	A41310
Order nr with water tank:	A413101
Operating pressure:	180 bar
Water output:	19 l/min
Nozzle size, DK:	07
Nozzle size, flat jet lance:	2507
Motor speed:	1400 rpm
Load:	400 v
Power intake:	7.5 Kw
Power output:	5.5 kw
Weight:	80 kg
Dimensions (mm):	780 x 700 x 360

### Equipment:

Total-Stop system with delayed motor cut-out:	Yes
Additional electrical over-current protection:	Yes
Water flow monitoring:	Yes / No
Water tank:	No / Yes
High pressure detergent:	No
High pressure hose:	A41081
Starlet trigger gun:	A123202
S/S lance with regulating nozzle:	A12395 - 2507

### Spare Parts:

Water seals:	A40517
Oil seals:	3 x A400441
Valves:	A400621
Un-loader valve:	A43444
In-line filter:	N/A
Pressure gauge:	A15039
On / off switch:	A411116
On / off switch cover:	A43453
Microswitch:	A15018
O ring on piston of UL:	A13159
Water inlet filter:	A13310

## The Stationary Hot Water Series



**Therm 895 ST**

### Technical Specifications:

Order nr:	A413525
Operating pressure:	195 bar
Water output:	14.9 l/min
Hot water output temp. °C:	12-86
Steam level, max °C:	155
Nozzle size, flat jet lance:	25045
Heating oil consumption at max. heating output, kg/h (l/h)	6.0 (7.1)
Heating oil consumption at 45°C, kg/h (l/h)	4.3 (5.1)
Heating output, Kw	65
Fuel tank capacity:	25
Motor speed:	1400 rpm
Load:	400 v
Power intake:	7.5 kw
Power output:	5.5 kw
Weight with hose reel:	235 kg
Dimensions (mm) L x W x H:	800 x 650 x 1600

### Equipment:

Total-Stop system with delayed motor cut-out:	Yes
Additional electrical over-current protection:	Yes
Water flow monitoring:	Yes
Water tank:	Yes
Photocell:	Yes
High limit thermostat:	Yes
Low level fuel cut out:	Yes
Operating hours meter:	Yes
High pressure detergent:	Yes
High pressure hose:	A41081
Starlet trigger gun:	A123202
S/S lance with flat jet nozzle:	A12392 - 25045

### Spare Parts:

Water seals:	A40517
Oil seals:	A400441
Valves:	A400621
Un-loader valve:	A44209
In-line fuel filter:	A44213
Pressure gauge:	A15039
On / off switch:	2 x A44835
Microswitch:	A15018
Green o ring (for lance):	A132731
Swashplate:	A40523 - 9.5°
Pistons:	A40505
O ring on piston of UL:	A13159
Water inlet filter:	A13310