

## THE THERM SERIES (HOT WATER)



Technical Specifications:	Therm CA 11/130	Therm C 11/130	Therm 635 -1	Therm 895 - 1
Order nr: (Without hose reel)	A41460	A41442	A41349	A41352
Order nr: (With hose reel):	A414601	A414421	A413491	A413521
Operating pressure:	130 bar	130 bar	130 bar	195 bar
Water output:	11 l/min	11 l/min	10.6 l/min	14.9 l/min
Hot water output temp. °C:	12-82	12-80	12-89	12-86
Steam level, max °C:	140	140	145	155
Nozzle size, flat jet lance:	25045	25045	25045	25045
Heating oil consumption at max. heating output, kg/h (l/h)	5.1 (6.1)	5.1 (6.1)	5.1 (6.1)	6.0 (7.1)
Heating oil consumption at 45°C, kg/h (l/h)	3.2 (3.8)	3.2 (3.8)	3.2 (3.8)	4.3 (5.1)
Heating output, Kw	55	55	55	65
Fuel tank capacity:	25	25	35	35
Motor speed:	1400 rpm	1400 rpm	1400 rpm	1400 rpm
Load:	230 v	230 v	230 v	400 v
Power intake:	3.4 kw	3.4 kw	3.4 kw	7.5 kw
Power output:	2.3 kw	2.3 kw	2.3 kw	5.5 kw
Weight with hose reel:	171 kg	179 kg	218 kg	223 kg
Dimensions (mm) L x W x H:	790 x 590 x 980	790 x 590 x 980	1050 x 800 x 1015	1050 x 800 x 1015

### Equipment:

Total-Stop system:	Yes (no time delay)	-	-	-
Total-Stop system with delayed motor cut-out:	-	Yes	Yes	Yes
Additional electrical over-current protection:	-	Yes	Yes	Yes
Water flow monitoring:	Yes	Yes	Yes	Yes
Photocell:	no	Yes	Yes	Yes
High limit thermostat:	no	Yes	Yes	Yes
Low level fuel cut out:	no	Yes	Yes	Yes
High pressure detergent:	Yes	Yes	Yes	Yes
High pressure hose, without reel / with reel:	A44878 (10m) A44879 (15m)	A44878 (10m) A44879 (15m)	A41081 (10m) A44381 (20m)	A41081 (10m) A44381 (20m)
Gun, S/S lance & flat jet nozzle:	A12486 - 25045	A12486 - 25045	-	-
Starlet trigger gun:	N/A	N/A	A123202	A123202
S/S lance with flat jet nozzle:	N/A	N/A	A12392 - 25045	A12392 - 25045
Parking brake:	Yes	Yes	Yes	Yes

### Spare Parts:

Water seals:	A410491	A410491	A410491	A40517
Oil seals:	3 x A41031	3 x A41031	3 x A41031	3 x A400441
Valves:	A417481	A417481	A417481	A400621
Un-loader valve:	A40490	A40490	A40490	A44209
In-line fuel filter:	A44213	A44213	A44213	A44213
Pressure gauge:	A15039	A15039	A15039	A15039
On / off switch:	2 x A44835	2 x A44835	2 x A44835	2 x A44835
Microswitch:	A15018	A15018	A15018	A15018
Green o ring (for lance):	A132731	A132731	A132731	A132731
Swashplate:	A40473 - 9.0°	A40460 - 9.0°	A40460 - 9.0°	A40523 - 9.5°
Pistons:	3 x A40455	3 x A40455	3 x A40455	3 x A40505
O ring on piston of UL:	A13159	A13159	A13159	A13159
Capacitor:	A43322	A43322	A43322	N/A
Water inlet filter:	A13310	A13310	A13310	A13310
Wheel:	4 x A46010	4 x A46010	4 x A44017	4 x A44017