

K 2000 SERIES

The Profi Series



Technical Specifications:

	K 2195 TS	K 2175 TS	K 2175 TST	Profi 160 TST
Order nr:	A417841	417821	417831	412301
Operating pressure:	180 bar	160 bar	160 bar	140 bar
Water output:	8 l/min	12 l/min	12 l/min	11 l/min
Suction height:	2.5m	2.5m	2.5m	2.5m
Nozzle size, DK:	03	03	042	042
Nozzle size, flat jet lance:	03 vario jet	042 vario jet	042 standard	042 standard
Motor speed:	1400 rpm	1400 rpm	1400 rpm	1400 rpm
Load:	230 v	230 v	230 v	230 v
Power intake:	3.2 kw	3.3 kw	3.3 kw	3.2 kw
Power output:	2.4 kw	2.6 kw	2.6 kw	2.5 kw
Weight:	37 kg	37 kg	39.5 kg	45 kg
Dimensions (mm):	375 x 360 x 900	375 x 360 x 900	375 x 360 x 900	375 x 360 x 900

Equipment:

Total-Stop system:	Yes	Yes	Yes	Yes
Hose reel:	No	No	Yes	Yes
Low pressure detergent:	Yes	Yes	Yes	No
High pressure hose:	A43416 (10m)	A43416 (15m)	A48015 (10m)	A43829 (15m)
Gun & 1/2 lance:	A12480	A12480	A12480	A12480
Dirt killer c/w s/s pipe:	410738 - 03	A41570 - 042	A41570 - 042	A41570 - 042
Flat jet nozzle c/w s/s pipe:	411562 - 03	A12701 - 042	A12701 - 042	A12393-042

Spare Parts:

Water seals:	A42911	A410491	A410491	A410491
Oil seals:	3 x A42907	3 x A41031	3 x A41031	3 x A41031
Valves:	A417481	A417481	A417481	A417481
Un-loader valve:	A40490	A40490	A40490	A40490
In-line filter:	A410462	A410462	A410462	A410462
Pressure gauge:	A15039	A15039	A15039	A15039
On / off switch:	A411116	A41751	A41751	A411116
On / off switch cover:	A43453	A43453	A43453	A43453
Microswitch:	A15018	A15018	A15018	A15018
Green o ring (for lance):	A132731	A132731	A132731	A132731
Swashplate:	A41028 - 14.3°	A41028 - 13°	A41028 - 13°	A41028 - 11.5°
Pistons:	3 x A42908	3 x A410321	3 x A410321	3 x A410321
O ring on piston of UL:	A13159	A13159	A13159	A13159
Capacitor:	A43322	N/A	N/A	A43322
Wheel:	A44538	A44538	A44538	A43817